



DRILL 2-<sup>1</sup>/<sub>16</sub> DIA HOLES IN THIS POSITION ON OUTLET SIDE OF FILTER. HOLES TO BE AS NEAR THREADED PORTION OF PT. 17 AS CONVENIENTLY POSSIBLE.

AGS 1002 PTN SHEET	DESCRIPTION	N° OFF	REMARKS
1 182	FILTER CASING.	1	
2 3	FILTER CASING.	1	
3 5	TOP FLANGE (INNER MEMBER)	1	
4 7	JOINTING WASHER	1	
5 5	TOP FLANGE (OUTER MEMBER)	1	
6 6	COLLAR (OUTER MEMBER)	1	
7 9	STIRRUP EYE BOLT.	1	
8 8	SPRING.	1	
9 8	STIRRUP.	1	
10 12	STRAINER UNIT.	1	ALTERNATIVE CONSTRUCTION
11 9	STIRRUP NUT.	1	NO ITEM 15
12 N.D.	LOCKWIRE 18 S.W.G. COPPER.		LENGTH TO SUIT.
13			
14 9	DISTANCE PIECE	1	
15 4	STRAINER UNIT.		BRASS WIRE & GAUZE.
16 6	COLLAR (INNER MEMBER.)	1	
17 7	FILTER SCREEN.	1	
18 10	TAB WASHER.	1	
19 10	UNION LOCK-NUT.	1	
20			
21			
22 11	D RING.	1	

**OBSOLESCENT - NO FURTHER MANUFACTURE - THIS ITEM MAY BE USED AS A PETROL FILTER ONLY UNTIL EXISTING STOCKS ARE EXHAUSTED - SUPERSEDED BY AGS. 1017**

TEST ASSEMBLED FILTER INTERNALLY WITH AIR AT 30 L<sup>B</sup>. PER SQ. IN. (GAUGE) PRESSURE WITH FILTER IMMERSSED IN PETROL OR PARAFFIN.

FOR PARTS 23 TO 37 INCLUSIVE, SEE A.G.S. 1002. SH. 12.

SCALE: - <sup>3</sup>/<sub>4</sub>, FULL SIZE.

9  
 AS N°  
 7  
 1001  
 1002  
 1003  
 1004  
 1005  
 1006  
 1007  
 1008  
 1009  
 1010  
 1011  
 1012  
 1013  
 1014  
 1015  
 1016  
 1017  
 1018  
 1019  
 1020  
 1021  
 1022  
 1023  
 1024  
 1025  
 1026  
 1027  
 1028  
 1029  
 1030  
 1031  
 1032  
 1033  
 1034  
 1035  
 1036  
 1037  
 1038  
 1039  
 1040  
 1041  
 1042  
 1043  
 1044  
 1045  
 1046  
 1047  
 1048  
 1049  
 1050  
 1051  
 1052  
 1053  
 1054  
 1055  
 1056  
 1057  
 1058  
 1059  
 1060  
 1061  
 1062  
 1063  
 1064  
 1065  
 1066  
 1067  
 1068  
 1069  
 1070  
 1071  
 1072  
 1073  
 1074  
 1075  
 1076  
 1077  
 1078  
 1079  
 1080  
 1081  
 1082  
 1083  
 1084  
 1085  
 1086  
 1087  
 1088  
 1089  
 1090  
 1091  
 1092  
 1093  
 1094  
 1095  
 1096  
 1097  
 1098  
 1099  
 1100