A.G.S. 2082

MAY BE SUPPLIED THUS



MARK	DIA 'A'	DIA 'B'	C	'D' RAD.	E	F	G	M	W
3		·389"	·25"	·05"	·05"	20 S.W.G.	·06"	·281"	·562" ·547"
4		·452"	·25"	·05"	·09"	20 S.W.G.	·06"	·281"	
5		·554"	·25"	·05"	·12"	20 S.W.G.	·08"	·281"	
6		·617"	·25"	·05"	·12"	20 S.W.G.	·08"	·281"	
7		·679"	·25"	·05"	·12"	20 S.W.G.	·08"	·281"	
8		·742"	·25"	·05"	·12"	20 S.W.G.	·08"	·281"	
9		·878"	·30"	·10"	·15"	18 S.W.G.	·10"	·281"	
10		·941"	·30"	·10"	·15"	18 S.W.G.	·10"	·281"	
12		1·066"	·30"	·10"	·15"	18 S.W.G.	·10"	·281"	
14		1·191"	·30"	·10"	·15"	18 S.W.G.	·10"	·281"	
16	1"	1·316"	·30"	·10"	·15"	18 S.W.G.	·10"	·281"	
18	1⅛"	1·441"	·30"	·10"	·15"	18 S.W.G.	·10"	·312"	·625" ·605"
20	1¼"	1·566"	·35"	·10"	·15"	16 S.W.G.	·10"	·312"	
22	1⅜"	1·691"	·35"	·10"	·15"	16 S.W.G.	·10"	·312"	
24	1½"	1·890"	·35"	·10"	·18"	16 S.W.G.	·12"	·312"	
26	1⅝"	2·020"	·35"	·10"	·18"	16 S.W.G.	·12"	·312"	
* 28	1¾"	2·230"	·40"	·125"	·22"	14 S.W.G.	·15"	·375"	·750" ·730"
* 30	1⅞"	2·355"	·40"	·125"	·22"	14 S.W.G.	·15"	·375"	
* 32	2"	2·480"	·40"	·125"	·22"	14 S.W.G.	·15"	·375"	

METHOD OF CALL UP :-

BASIC PART NUMBER	NOMINAL PIPE DIA. IN SIXTEENTH OF AN INCH. (MARK)

A.G.S. 2082 - 7

SUITABLE FOR CONTACT WITH FUEL, OIL & SYNTHETIC LUBRICANTS, INCLUDING EEL 3.
STRIP TO BE RED ANODISED AFTER RUBBERING.

* MARKS 28, 30 & 32 ARE OBSOLESCENT AND ARE SUPERSEDED BY THE SAME MARK NUMBERS ON A.G.S. 5431.

1										
2	F.33									
3	S.M.G.									
4	F.1	S.M.2024								

RUBBER CODE H.X.C.
ALUM. ALLOY CLIP L.72

USED ON										
	HT		PT	SEE ABOVE	SCALE		UNLESS OTHERWISE STATED	± ·010"	THIRD ANGLE PROJECTION.

ISSUED BY THE SOCIETY OF BRITISH AIRCRAFT CONSTRUCTORS LTD., 29, KING STREET, ST. JAMES', LONDON, S.W.1

ORIGINATED	DRAWN	TRACED	CHECKED	APPROVED FOR	DATE
DUNLOP F.A.C.	F.A.C.	F.A.C.			

PIPE CLIP RUBBER COVERED FOR ¼ DIA. FIXING.

A.G.S. 2082