



MAY BE SUPPLIED

THIS DRG. SUPERSEDES M/RKS 28-30-32 ON AGS. 2082.

SM 2024

MARK	NOM. PIPE DIA. A.	B DIA.	C	D RAD.	E	F	G	M RAD.	W
28	1 3/4"	2.230"	.50"	.250"	.22"	14 SWG.	.15"	.375"	
30	1 7/8"	2.355"	.50"	.250"	.22"	14 SWG.	.15"	.375"	750°
32	2"	2.480"	.50"	.250"	.22"	14 SWG.	.15"	.375"	730°

METHOD OF CALL UP.

BASIC PART NUMBER. NOMINAL PIPE DIA. IN SIXTEENTH OF AN INCH. (MARK)

AGS. 3431-30.

SUITABLE FOR CONTACT WITH FUEL, OIL & SYNTHETIC LUBRICANTS, INCLUDING EEL.3.
STRIP TO BE RED ANODISED AFTER RUBBERING.

REF.	DRAWING OR PART No.	DESCRIPTION	RUBBER CODE	ALUMM. ALLOY CLIP	UNIT QTY	MATERIAL-REMARKS
			RUBBER CODE			HXC
			ALUMM. ALLOY CLIP			L.72

DESIGNED	DRAWN	TRACED	CHECKED	APPROVED FOR	DATE
DUNLOP	F.A.L.	F.A.L.	F.A.L.	<i>W. Blundy</i>	23-4-63

ISSUED BY THE SOCIETY OF BRITISH AEROSPACE COMPANIES LTD.,
29, KING STREET, ST. JAMES'S, LONDON, S.W.1.

HT	PT	AS ABOVE	SCALE	LIMITS NOT SHOWN	+ .010"	THIRD ANGLE PROJECTION.
						A.G.S. 3431.

PIPE CLIP RUBBER COVERED FOR 1/4" DIA. FIXING. (FOR PIPES 1 3/4" DIA. & OVER)