DESIGNED DRAWN TRACED CHECKED APPROVED FOR PROOF AGAINST FUELS, OILS & LUBRICANTS 1/4 INCREMENTS INCLUDING E.E.L. 3, CAN BE USED UP TO 300°C. TAPE LENGTH IN DIAMETER THICKNESS IT IS RECOMMENDED THAT THESE TAPES BE PURCHASED IN ROLLS OF 12 YDS. MINIMUM, THEREAFTER IN TAPE MUST BE ORDERED AS FOLLOWS: TAPE TO A.G.S. 3441/MARKINGS SPECIFIED / THICKNESS (LE. 003" OR 007 THE APPROPRIATE CLIPS SEPARATELY. NCREMENTS OF 6 YDS. I.E. 12,18,24 YDS. ETC. WHEN ORDERING ROLLS OF TAPE IT WILL BE NECESSARY TO ORDER SR62 THICK) E.G. 12 YDS, OF TAPE TO A.G.S. 3441 / MARKINGS SPECIFIED / 003. ISSUED BY THE SOCIETY OF BRITISH AIRCRAFT CONSTRUCTORS LTD., 19, KING STREET, ST. JAMES'S, LONDON, S.W.I. 43658361141513 2242523 8 10 11 13 14 16 17 21 24 27 30 33 37 40 43 003 ON DRAWINGS. MARKINGS TO BE SPECIFIED 007 LAMOLUM 27.4.63 CONTACT SURFACE COATED WITH NON-SLIP MATERIAL TO AID WRAPPING. DATE w. PIPE IDENTIFICATION BAND FOR USE IN HOT ZONES. 1/2" WIDE N SEE A.G.S. 100 FOR GENERAL INFORMATION I.E. TAPE TO SUIT 3/4"O. D. PIPE WILL BE AGS. 3441/14. PART No./TAPE LENGTH IN 1/4 OF AN INCH METHOD OF CALLING UP: DRAWING OR PART No. AGS.2095. CLIP FOR USE WITH 003 THICK TAPE. AGS. 2117. 50 7 NONE SCALE CLIP FOR USE WITH .007"THICK TAPE. P.T.F.E. IMPREGNATED GLASS FABRIC TAPE **EXCESS TAPE** DESCRIPTION APPLICATION METHOD OF NE E DNAWN HAND MATERIAL - REMARKS A.G.S. 344 THIRD ANGLE PROJECTION. ISSUE ALT.