



LENGTH	N° 3				
	PART NUMBERS				
1/4"	12				
3/8"	13				
1/2"	14				

SPECIFICATION:- THE MATERIAL SHALL BE MILD STEEL, LIMITED TO SULPHUR .05% (MAXIMUM) AND PHOSPHOROUS .07% (MAXIMUM).

THE WIRE IN THE ANNEALED STATE SHALL GIVE 22/28 TONS PER SQ. INCH TENSILE AND 20/26% ELONGATION ON 8 DIAMETERS.

EACH SCREW SHALL BE CAPABLE OF BEING BENT THROUGH AN ANGLE OF 45° ON THE THREADED PORTION, OVER A RADIUS EQUAL TO THE DIAMETER OF THE SCREW WITHOUT BREAKING.

FINISH - TO BE CADMIUM PLATED TO SPEC: D.T.D 904 (LATEST ISSUE).

ISSUE N°	14 19 23 3								
ALTERATION N°	A.S. N° AGS/693								
ISSUED BY ROYAL AIRCRAFT ESTABLISHMENT	TITLE:- COUNTERSUNK WOODSCREWS FOR SECURING METAL SHEATHS TO WOODEN AIRSCREWS						DRAWN G.H. ARMSTON	RE-TRACED G.H.F. D.H.P. 12.12.49	
	ISSUE N°						CHECKED S. STARR.	APPROVED G.W. 3-7-50	
	ALTERATION N°						RE-CH		