



Screws are to be marked with a ring stamped on the upper face of the head for identification purposes except Nos 2, 4 and 6.

Non-Corrodible Steel.

Length.	N°2	N°4	N°6	N°8	N°10	N°12	N°14	N°16
	Part Numbers.							
$\frac{1}{4}$ "	1	18	35	52				
$\frac{5}{16}$ "	1A							
$\frac{3}{8}$ "	2	19	36	53	70			
$\frac{1}{2}$ "	3	20	37	54	71	88	105	
$\frac{5}{8}$ "	4	21	38	55	72	89	106	123
$\frac{3}{4}$ "	5	22	39	56	73	90	107	124
$\frac{7}{8}$ "	6	23	40	57	74	91	108	125
1"	7	24	41	58	75	92	109	126
$1\frac{1}{4}$ "	8	25	42	59	76	93	110	127
$1\frac{1}{2}$ "	9	26	43	60	77	94	111	128
$1\frac{3}{4}$ "	10	27	44	61	78	95	112	129
2"	11	28	45	62	79	96	113	130
$2\frac{1}{4}$ "		29	46	63	80	97	114	131
$2\frac{1}{2}$ "		30	47	64	81	98	115	132
$2\frac{3}{4}$ "		31	48	65	82	99	116	133
3"		32	49	66	83	100	117	134
$3\frac{1}{2}$ "			50	67	84	101	118	135
4"				68	85	102	119	136
A				.14"	.17"	.20"	.23"	.25"
B				.01"	.015"	.02"	.02"	.02"

Specification :- The material to be non-corrodible steel wire to D.T.D. specification N° 189 (latest issue).

ISSUED BY DRAWING OFFICE DIRECTORATE OF TECHNICAL DEVELOPMENT. AIR MINISTRY.	TITLE: STANDARD COUNTERSUNK HEAD WOODSCREWS.				DRAWN J. M. THOMSON	RETRACED 18-1-39
	ISSUE N°	X	2		CHECKED J. H. BRASHER	APPROVED. G. W. 30-5-33.
	ALTERATION N°	AGS/281	AS- AGS/134		RE-CHECKED G. T. REYNOLDS	