



MARK	A	B	C	D	E	F TO SUIT STEEL WIRE ROPE TO BS SPEC. W.11	
						DIA	MINIMUM BREAKING LOAD.
A	.35"	.70"	.12"	.080"	24 SW.G.	.08"	5 CWTS.
B	.40"	.80"	.17"	.110"	24 SW.G.	.15"	15 CWTS.
C	.50"	1.00"	.21"	.135"	22 SW.G.	.18"	25 CWTS.
D	.60"	1.20"	.24"	.155"	20 SW.G.	.21"	30 CWTS.
E	.70"	1.40"	.27"	.170"	20 SW.G.	.24"	40 CWTS.
F	.80"	1.60"	.30"	.190"	20 SW.G.	.28"	65 CWTS.
G	.90"	1.80"	.33"	.210"	18 SW.G.	.31"	73 CWTS.

MATERIAL:- NON-CORRODIBLE STEEL SHEET TO SPEC:
D.T.D. 171, (LATEST ISSUE)

SM 598

TITLE THIMBLES. NON-CORRODIBLE STEEL.		ISSUE 3					
MINISTRY OF SUPPLY		ALT. No AS/AGS 911					
APPLICATIONS FOR A.G.S. SHEETS TO:- ATR.4A. THAMES HOUSE, MILLBANK, S.W.1.		R.A.E. APPROVAL		A.D.S.A.E. APPROVAL			
GENERAL INQUIRIES TO:- A.D.S.A.E. THAMES HOUSE, MILLBANK, S.W.1.		SIGNATURE <i>C. S. Rowell</i>	DATE 29.4.52.	SIGNATURE <i>G. T. Tarrant</i>	DATE 7/7/52		
		SHEET NO 1	A.G.S. No 969.				
		NO OF SHEETS 1					