BRITISH STANDARDS INSTITUTION

BRITISH STANDARDS HOUSE, 2 PARK STREET, LONDON, W.1

INCORPORATED BY ROYAL CHARTER Telephone: 01-629 9000 Telegrams: STANDARDS LONDON WI

BRITISH STANDARD : AEROSPACE SERIES SPECIFICATION FOR

ALUMINIUM-COPPER-MAGNESIUM-MANGANESE ALLOY PLATE

(Solution treated, controlled stretched and aged at room temperature)

(Cu 4·4, Mg 1·5, Mn 0·6)

NOTE 1. This British Standard covers plate, including that which has been forged as an intermediate operation, which is finished by hot or cold rolling. It does not cover forged plate.

NOTE. 2. If material to this British Standard is re-solution treated but not again controlled stretched, it must be regarded as being in the solution treated and aged at room temperature, but not controlled stretched, condition, even though the specified mechanical properties are obtained. Plate of this composition in that condition is covered by British Standard L.98.

NOTE 3. The specified chemical composition and mechanical properties meet the requirements of A.I.C.M.A. Recommendation AL.P13.

NOTE 4. Where British equivalents are stated, the figures in metric units are to be regarded as the standard. The conversions are approximate. More accurate conversions should be based on the tables in BS 350 'Conversion factors and tables'.

1. INSPECTION AND TESTING PROCEDURE

This British Standard shall be used in conjunction with Sections One and Fourteen of British Standard L.100.

2. QUALITY OF MATERIAL

The material shall be made from aluminium complying with the requirements of British Standards L.31, L.48 or L.49 and alloying constituents, with or without approved scrap, at the discretion of the manufacturer.





L. 97, February, 1968

3. CHEMICAL COMPOSITION

The chemical composition of the material shall be:

	Per cent			
Element	min.	max.		
Copper	3.8	4.9		
Magnesium	1.2	1.8		
Silicon		0.50		
Iron		0.50		
Manganese	0.30	0.9		
*Nickel		0.05		
*Zinc	_	0.2		
*Lead		0.05		
*Tin		0.05		
*Titanium plus Zirconium		0.20		
*Chromium		0.10		
Aluminium		The remainder		

^{*}Subject to the discretion of the Inspecting Authority, determination of these elements need be made on a small proportion only of the samples analysed.

4. CONDITION

The material shall be supplied solution treated, controlled stretched to a permanent extension of not less than $1\frac{1}{2}\frac{9}{6}$ nor more than $2\frac{1}{2}\frac{9}{6}$, and aged at room temperature. No other condition of supply is permissible.

5. HEAT TREATMENT

The material shall be heat treated as follows:

- (1) Solution treat by heating at 495 \pm 5°C. Quench in water at a temperature not exceeding 40°C.
- (2) Age at room temperature for not less than 48 hours.

6. MECHANICAL PROPERTIES

Tensile test. The mechanical properties obtained from test pieces selected and prepared in accordance with the relevant requirements of British Standard L.100 shall be not less than the following values:

Nominal thickness	Direction	0·2% proof stress		Tensile strength		Elongation
		kgf/mm²	tonf/in²	kfg/mm²	tonf/in²	%
6 mm (0·24 in) up to and including 12 mm (0·47 in)	Long transverse	29	18.4	44	27.9	10
Over 12 mm up to and including 25 mm (0.98 in)	Long transverse	29	18.4	44	27.9	10
Over 25 mm up to and including 40 mm (1.57 in)	Longitudinal	32	20·3	44	27·9	12
	Long transverse	29	18·4	43	27·3	9
	Short transverse	27	17·1	39	24·8	3·5
Over 40 mm up to and including 63 mm (2.48 in)	Longitudinal	32	20·3	44	27·9	12
	Long transverse	28	17·8	42	26·7	9
	Short transverse	27	17·1	39	24·8	3·5
Over 63 mm up to and including 90 mm (3.54 in)	Longitudinal	32	20·3	44	27·9	10
	Long transverse	28	17·8	42	26·7	8
	Short transverse	27	17·1	38	24·1	3·5
Over 90 mm up to and including 115 mm (4.53 in)	Longitudinal	32	20·3	44	27·9	10
	Long transverse	28	.17·8	41	26·0	8
	Short transverse	25	.15·9	38	24·1	3·5
Over 115 mm up to and including 140 mm (5.51 in)	Longitudinal	32	20·3	42	26·7	8
	Long transverse	27	17·1	40	25·4	7
	Short transverse	25	15·9	38	24·1	3·5

This British Standard, having been approved by the Aerospace Industry Standards Committee and endorsed by the Chairman of the Engineering Divisional Council, was published under the authority of the General Council of the Institution on 22nd February, 1968.

The Institution desires to call attention to the fact that this British Standard does not purport to comprise all the necessary provisions of a contract.

British Standards are revised, when necessary, by the issue either of amendment slips or of revised editions. It is important that users of British Standards should ascertain that they are in possession of the latest amendments or editions.

The following BSI references relate to the work on this standard: Committee reference ACE/24. Draft for comment 67/8971.

SBN: 580 00063 X